

EB-1795F

The Epson EB-1795F series packs superior imaging quality along with a suite of connectivity and usability features into a body weighing only 1.83kg and 44mm slim. The EB-1795F series comes with Gesture Presenter technology, which allows you to move between slides without a clicker. Lastly, with Epson's 3LCD technology that delivers up to 3 times brighter colours you can astound audiences anywhere you go.







Correction









## **Ultra Portability**

Deliver impactful presentations on-the-go with a projector that is 1.83 kg, 44 mm slim, and fits perfectly into your laptop bag.

## **Horizontal and Vertical Keystone Correction**

A feature that helps align slides and images, and correct distortions effortlessly.

## **Colour Brightness**

Boasting up to 3 times brighter colours gamut and brightness, with no rainbow effect, images are brought to life in realistic and vibrant hues.



MODEL NUMBER Projection Technology Specifications of Main Parts		EB-1795F
		RGB liquid crystal shutter projection system
	Native Resolution	1080p
Projection Lens	Туре	Optical Zoom (Manual) / Focus (Powered)
	F-Number	1.58 - 1.70
	Focal Length	14.06 - 16.82 mm
	Zoom Ratio	1-1.2
	Throw Ratio	1.02 - 1.23 (Wide to Tele)
Lamp	Туре	214 W UHE
	Life (Normal / Eco)*1	4,000 / 7,000 hours
Screen Size (Project		
Zoom: Wide		30" - 300" [76.2 - 762 cm]
Zoom: Tele		30" - 300" [76.2 - 762 cm]
Standard Size		60" screen (1.35 - 1.64 m)
Brightness*2		
White Light Output (Normal)		3,200 lm
Colour Light Output (Normal / Eco)		3,200 lm / 1,900 lm
Contrast Ratio	Voirridi / Looj	
Auto Iris: On		10,000:1
Colour Mode		Dynamic, Presentation, Cinema, sRGB, Blackboard, DICOM SIM
Internal Speaker(s)		. Dynamic, Presentation, Otherna, shob, blackboard, bloom shift
Sound Output		Monaural: 1 W x 1
Keystone Correctio	n	•
Vertical / Horizontal Keystone		±45°/±30°
Auto Keystone Correction		yes (horizontal and vertical) between 30"-100" for throw distance between 68 cm – 226 cm, vertical ± 30° horizontal
, ale rejectic conceler.		± 20°
Connectivity		-
Analog RGB Input	D-Sub 15Pin	1 (Blue)
Video Input	Composite	RCA x 1
Digital Input	HDMI	1 (MHL)
Audio Input	Stereo Mini Jack	1
USB Input	USB Type A	1 (USB Memory, USB Document Camera, Wireless LAN Firmware Update)
	USB Type B	1 (USB Display, Mouse, KB, Control, Firmware Update)
Network	Wireless LAN	In-built
Operating Temperature		5 - 40 °C <41 - 104 °F> (0 m / 0 ft to 2,286 m / 7,500 ft) 5 - 35 °C <41 - 95 °F> (over 2,286 m / 7,500 ft) (20% - 80% humidity, No condensation)
Operating Altitude		0 - 3,000 m (0 - 9,842 ft) (over 1,500 m / 4,921 ft: with high-altitude mode)
Direct Power On / Off		Yes / Yes
Start-Up Period		About 7.2 seconds, Warm-up Period: 30 seconds
Cool Down Period		Instant Off
Power Supply Voltage		100 - 240 V AC ±10%, 50/60 Hz
Power Consumptio	-	100 210 1710 210 701 00 00 112
Lamp On (Normal / Eco)		295 W / 208 W
Standby		0.34 W
Dimension Excluding Feet (D x W x H)		- 0.34 W - 213 x 292 x 53 mm
Weight		
		Approx. 1.83 kg
Fan Noise (Normal / Eco)		39 dB / 30 dB



Power Cable: 3 m

Remote Control: Yes, with Alkaline AA Battery

FB-1795F



©2020 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Android is a trademark of Google Inc.

Information correct as at November 2020

#### EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-4566 5000 Fax: 080-4566 5005

# Regional Offices:

Ahmedabad 3314 8500/01, Chennai 3967 7500, Cochin 4012 315, Coimbatore 98942 19200 Hyderabad 4857 0032, Jaipur 78699 11699, Kolkata 4603 4729, Mumbai 3079 8200 New Delhi 3312 0300, Pune 3028 6000/05,





**Epson Helpline:** For product info or service- 1800 425 0011 For service - 1800 123 001 600 (9AM - 6PM) (Mon - Sat)

Email: emp@eid.epson.co.in www.epson.co.in

Dealer's Stamp

Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time

<sup>&</sup>lt;sup>2</sup> Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.